



Project Name: _____

Location: _____

Item #: _____

© LPL04/2021

PBF 18.0 Blast Chiller/Freezer

BLAST CHILLER/FREEZER SPECIFICATIONS

This unit fits perfectly into a professional kitchen workflow, making it possible to practice HACCP guidelines concerning the cook/chill concept. The unique ambient chill method and indirect air circulation help to assure better food quality and safety.

Manufactured with the environment in mind, it includes advanced technology and important features to protect your long-term investment. Along with colder product temperatures, it offers lower utility costs, improved food safety and an excellent value in today's foodservice marketplace.

CAPACITY

18 pans 18" x 26" x 1" deep
Pans not included

DISTANCE between shelves 2.69"

OUTSIDE DIMENSIONS

32.25" (W) X 35" (D) X 87.75" (H)

INTERIOR DIMENSIONS

27.5" (W) X 19.5" (D) X 52" (H)

WEIGHT: 620 lbs

SHIPPING DIMENSIONS:

34" (W) X 38" (D) X 93" (H)

SHIPPING WEIGHT: 660 lbs

OUTPUT CHILLING CAPACITY

+194/+37°F 200 lbs within 90 minutes

OUTPUT FREEZING CAPACITY

+194/0°F 100 lbs within 240 minutes

OUTPUT THAWING CAPACITY

0°F/38°F 40 lbs within 240 minutes

0°F/38°F 80 lbs within 480 minutes

0°F/38°F 120 lbs within 720 minutes

HEAT LOAD BTU/HR: 18,420

- 10° F evaporator temperature/104° F ambient

ELECTRICAL SUPPLY:

208-240 V/1 PH/60 Hz (3 PH optional)

RLA/LRA/MOP: 12/102/34

60 A circuit, # 6 wire required

STANDARD FEATURES

- Ambient chill method
- Indirect air circulation to improve food quality
- HACCP compliant; self-contained refrigerated system
- Electronic touch screen control; user friendly and programmable for up to 99 recipes
- USB port; front mounted for easy access to download data, such as HACCP, or upload recipes
- Automatic hot gas defrost
- Rounded interior corners for simple cleaning
- Single point product probe
- Slide out refrigeration system for efficient service access
- Stainless steel rack system for pans or shelves
- Snap-in magnetic gasket for straightforward changes or cleaning
- Self-closing door, right-hand hinged
- Casters for effortless movement, front casters can be swivel, fixed or locked
- 304 Stainless steel interior and exterior front, sides, and top.
- Refrigerant: R404
- Environmentally friendly HFO insulation

WARRANTY

- Three year warranty on parts and labor
- Additional warranty for years 3-5 on compressor (parts only)

OPTIONAL ACCESSORIES

- Plastic coated shelves
- UV sanitizer
- Heated multi-point probe
- Three core probe kit
- Left-hand door
- Door bolt lock



Superior Quality
Made in Italy

Specifications subject to change without notice.



Proud to be family-owned.

