



PrepRite PBF15.0

ELEVATE YOUR FOOD PRESERVATION STANDARDS

This unit fits perfectly into a professional kitchen workflow, making it possible to practice HACCP guidelines concerning the cook/chill concept. The unique ambient chill method and Indirect air circulation help to assure better food quality and safety.

Manufactured with the environment in mind, it includes advanced technology and important features to protect your long-term investment. Along with colder product temperatures, it offers lower utility costs, improved food safety and an excellent value in today's foodservice marketplace.



Advanced Technology for Food Quality & Safety

The PBF15.0 utilizes an ambient chill method and indirect air circulation to improve food quality and safety. It is HACCP compliant and features a self-contained refrigerated system.



Efficient & Environmentally Friendly Design

The PBF15.0 is designed with rounded interior corners for simple cleaning, a slide-out refrigeration system for efficient service access, and environmentally friendly HFO insulation. It also features a stainless steel rack system for pans or shelves and casters for effortless movement.



User-Friendly & Programmable Controls

The unit comes with an electronic touch screen control that is user-friendly and programmable for up to 99 recipes. It also includes a USB port for easy access to download data, such as HACCP, or upload recipes.



Standard Features

- Ambient chill method
- Indirect air circulation to improve food quality
- HACCP compliant; self-contained refrigerated system
- Electronic touch screen control; user friendly and programmable for up to 99 recipes
- USB port for easy access for HACCP data, or upload recipes
- Automatic hot gas defrost
- Rounded interior corners for simple cleaning
- Slide out refrigeration system for efficient service access
- Stainless steel pan rack system accommodating both 18"x26" Sheet Pans or 12"x20" Hotel Pans
- Snap-in magnetic gasket for straightforward changes or cleaning
- Single point product probe
- Self-closing door, right-hand hinged
- Casters for effortless movement, front casters can be swivel, fixed or locked
- 304 Stainless steel interior and exterior front, sides, and top.
- Refrigerant: R404
- Environmentally friendly HFO insulation

Warranty:

- Three year warranty on parts and labor
- Additional warranty for years 3-5 on compressor (parts only)

Product Yield:

OUTPUT CHILLING CAPACITY

- +194/+37°F 110 lbs within 90 minutes

OUTPUT FREEZING CAPACITY

- +194/0°F 70 lbs within 240 minutes

OUTPUT THAWING CAPACITY

- 0°F/38°F 22 lbs within 240 minutes
- 0°F/38°F 44 lbs within 480 minutes
- 0°F/38°F 66 lbs within 720 minutes

Optional Accessories:

- Plastic coated shelves
- UV sanitizer
- Heated multi-point probe
- Three core probe kit
- Left-hand door
- Door bolt lock



CROWNTONKA® ICS® LOTEMP DOORS™ PREPRITE® SMARTRITE® THERMALRITE®

Proud to be family-owned.