

PREPRITE BLAST CHILLER CLEANING & MAINTENANCE CHECKLIST

DAILY CLEANING CHECKLIST

INTERIOR SURFACES

- Wipe all interior walls, corners, ceiling, & floor with warm water & a mild, non-chlorinated detergent
- Rinse thoroughly & sanitize to prevent bacterial growth
- Dry all surfaces completely

FOOD PROBES

- Clean & sanitize probes after each blast cycle
- Ensure probes are dry before storage or reuse

DOOR GASKETS

- Wipe gaskets with warm, soapy water
- Remove debris & food residue to maintain a tight seal

DRAIN LINES & DRAIN PAN

- Inspect for clogs, standing water, or odors
- Clean as needed to prevent buildup

DEFROST & DRYING

- Confirm defrost/sanitation cycle is completed at end of day
- Leave door slightly ajar when unit is not in use to allow moisture to evaporate

EXTERIOR SURFACES

- Wipe exterior with warm water & mild detergent
- Avoid abrasive pads or cleaners

WEEKLY CLEANING & INSPECTION

SHELVES, RACKS & ACCESSORIES

- Remove shelves & racks
- Wash in sink with hot, soapy water
- Rinse, sanitize, & air-dry before reinstalling

AIRFLOW & CLEARANCE CHECK

- Ensure required ventilation clearances are maintained
 - Minimum 4" from back & sides
 - Minimum 12" from front
- Confirm unit is not tight against walls or heat-producing equipment

SERVICE ACCESS AREAS

- Ensure all access panels & service areas remain unobstructed

EXTERIOR STAINLESS STEEL

- Clean with approved stainless steel cleaner
- Wipe in direction of the grain

PREPRITE BLAST CHILLER CLEANING & MAINTENANCE CHECKLIST

MONTHLY / PERIODIC MAINTENANCE

CONDENSER COIL (EVERY 30–90 DAYS OR AS NEEDED)

- Frequency may increase in dusty, flour-heavy, or powder-rich environments
- Remove front louver panel
- Vacuum and gently brush dust and debris from condenser coils
- ⚠ Do NOT use caustic cleaners on condenser coils
- ⚠ Cleaning should be performed by a qualified service technician

SAFETY & IMPORTANT NOTES (REVIEW REGULARLY)

- Disconnect power before performing maintenance beyond daily wipe-downs
- Do NOT use pressure washers or high-pressure water
- Avoid chlorine, hydrochloric acid, or abrasive cleaners
- Do NOT clean condenser coils with caustic chemicals
- Maintain proper airflow clearances at all times
- Ensure access for service and maintenance is never blocked
- Only qualified service personnel should perform condenser or internal mechanical maintenance

BEST PRACTICES

- Maintain a cleaning & maintenance log
- Increase condenser cleaning frequency in dusty environments
- Contact authorized service if you notice reduced performance, excessive frost build-up, unusual noises, or temperature inconsistencies.